



CATALOGO PRODOTTI

MULTIVOLTAGE STATIC FEEDER FOR RAILWAY CARRIAGE TESTING



The purpose of the apparatus is to provide, from the mains voltage 400V, the four voltages employed on the European carriage: 3000Vdc, 1500Vdc, 1500Vac and 1000Vac 16,6Hz. These voltages are stabilized and manually settable.

MULTIVOLTAGE STATIC FEEDER FOR RAILWAY
CARRIAGE TESTING**TECHNICAL DATA**

1. INPUT

- Input voltage:	400V 3F
- Input voltage range:	± 15%
- Input frequency:	± 5%
- Rated power:	100kW

2. OUTPUT

OUTPUT VOLTAGE 1:	3000Vdc
- Range settable:	1620Vdc ÷ 4255Vdc
- Static stability:	± 1,5%
- Dynamic stability (with load variation ± 60%):	± 8%
- Ripple (RMS):	4%
- Overload for 10 minutes:	125%
- Short circuit current:	150%
OUTPUT VOLTAGE 2:	1500Vcc
- Range settable:	1620Vdc ÷ 4255Vdc
- Static stability:	± 1,5%
- Dynamic stability (with load variation ± 60%):	± 8%
- Ripple (RMS):	4%
- Overload for 10 minutes:	125%
- Short circuit current:	150%
OUTPUT VOLTAGE 3:	1500V single phase
- Range settable:	1140Vac ÷ 1760Vac
- Nominal frequency:	50Hz ± 0,5Hz
- Waveform:	sinusoidal
- THD:	5%
- Static stability:	± 1,5%
- Dynamic stability (with load variation ± 60%):	± 8%
- Overload for 10 minutes:	125%
- Short circuit current:	150%
OUTPUT VOLTAGE 4:	1000V single phase
- Range settable:	600Vac ÷ 1100Vac
- Nominal frequency:	16,6Hz ± 0,5Hz
- Waveform:	sinusoidal
- THD:	5%
- Static stability:	± 1,5%
- Dynamic stability (with load variation ± 60%):	± 8%
- Overload for 10 minutes:	125%
- Short circuit current:	150%



MULTIVOLTAGE STATIC FEEDER FOR RAILWAY
CARRIAGE TESTING

3. MISCELLANEOUS

- Range working temperature:	-5°C ÷ +45°C
- Max temperature daily average:	35°C
- Altitude without downgrading:	1000m
- Relative humidity at 45°C without condensing:	90%
- Dimensions:	2000x950x1850mm
- Weight:	1500kg
- Losses:	10kW

4. METERS

- DC voltmeter
- DC amperometer
- AC voltmeter (50Hz, 16,6Hz)
- AC amperometer (50Hz, 16,6Hz)
- Frequency meter

5. SIGNALLING

- Working converter
- Fault converter
- Overtemperature
- 3000Vdc switch on
- 1500Vdc switch on
- 1500Vac 50Hz switch on
- 1000Vac 16,6Hz switch on

6. REMOTE CONTROL (OPTIONAL)

- Working converter
- Fault converter
- Overtemperature
- 3000Vdc switch on
- 1500Vdc switch on
- 1500Vac 50Hz switch on
- 1000Vac 16,6Hz switch on

7. LOCAL CONTROLS

- Key selector 3000Vdc selection
- Key selector 1500Vdc selection
- Key selector 1500Vac 50Hz selection
- Key selector 1000Vac 16,6Hz selection
- Calibration 3000Vdc
- Calibration 1500Vdc
- Calibration 1500Vac 50Hz
- Calibration 1000Vac 16,6Hz



CATALOGO PRODOTTI

MULTIVOLTAGE STATIC FEEDER FOR RAILWAY
CARRIAGE TESTING

8. SWITCHES

- Input automatic breaker with locked key.
- Output switch at two positions: output connected to converter/ output connected to the ground. Double locked keys with keys switched and locked for on position.



LISA CONTROL TECHNOLOGY CO., LTD
Unit 202, CT4A2, Bac Linh Dam Urban, Dai Kim, Hoang Mai district,
Hanoi, Vietnam
Tel:+84 4 354 00982 **Fax:** +84 4354 00982
Email: contact@lisatech.vn